

Flatwork Ironer

Y-3300 series

*Grouping setting and special tiny shake roller device of the small diameter combined type heated rollers, make the linen surface more smoothly and brightly.

*Using new type of roller setting pressed by two sides and lead belts, raise the ironing quality.

*Automatic adjusting device can automatic continually adjust the heated belts, preventing from appearing belts imprints

*Small diameter heated roller structure, running smoothly, reliable and accurate, save place, high speed production capacity.

*hommization touch panel design, using frequency conversion continuous variable speed, according to different linen, can edit 15 types of ironing speed and temperature program.

*Machine has been fixed hand guard device and urgent stop button, ensuring the operation safety and reliability.



Mode		Y-3300IV Z	Y-3300VI Z
Heated roller		4 PCS	6 PCS
Heated roller size	Diameter(mm)	Φ 650	
	Width(mm)	3,330	
Pipe diameter	Steam inlet(A)	50	
	Steam outlet(A)	40	
	Compressed air(A)	10	
Motor capacity(kw)		3.75	
Belt speed adjustment range(m/min.)		3 to 50	
Steam pressure	Normal	0.8MPa	
	Max.	0.97MPa	
Equipment capacity	Steam(kg/h)	530	690
	Electricity(KAV)	4	
Steam consumption(kg/h)		290	390
Compressed air consumption(NL/H)		13	14
Power supply		3 ph 220V/380V 50/60Hz	
Distributed electricity(mm ²)		3.5	
Maximum current(A)		16/9	
Dimension	Width(mm)	4,610	
	Length(mm)	3,610	5,110
	Height(mm)	1,700 (max. size include signal light: 2,240mm)	
Net weight(kg)		6,550	9,300